



CHARACTERISTICS

- NON TOXIC POLYETHYLENE
 - KINK PROOF FOR ALL KINDS OF TUBES
 - PROTECTS FROM ABRASION AND BREAKAGE
 - NATURAL OR BLACK ++ COLORS IN STOCK
- ++ resists ultra violet rays

POLY-SPIRAL TUBING WRAP

PART#	TUBE O.D.	REPLACE WITH COLOR CODE	
PS-140-**	1/4	NATURAL	00
PS-120-**	1/2	BLACK	01
PS-340-**	3/4		

POLYURETHANE COILED TUBING

CHARACTERISTICS

- MORE USABLE LENGTH (80%) THAN NYLON
- HIGHLY KINK AND ABRASION RESISTANT
- SUPERIOR OIL RESISTANCE; COMPLY WITH RMA'S CLASS B DESIGNATION
- STANDARD PIGTAILS ARE 4" ONE END, 20" THE OTHER, AND CAN BE TRIMMED TO SUIT THE APPLICATION
- TEMPERATURE RANGE: 0° TO 150° F
- READY MADE ASSEMBLIES WITH 3/8" SWIVELS EACH END.



PART #	I.D.	O.D.	WORKING LENGTH	ACTUAL LENGTH	MAX PSI @70°F	MAX PSI @122°F	COIL O.D.
URC04X15	1/4	.375	12	15	125	75	2"
URC04X25	1/4	.375	20	25	125	75	2"
URC06X15	3/8	.570	12	15	100	60	3"
URC06X25	3/8	.570	20	25	100	60	3"